



Robopacker T2

Automatic bundle counting, squaring and strapping behind a multipoint folder gluer.

- Fully automatic mode for straight line and 4/6 corner boxes
- With robotic rotating and stacking capability for crashlock bottom boxes
- 100 % Automatic setup with memorization

Specifications:

Type:

Robopacker T2: Left and right outfeed
Set-Up: Fully automatic

Boxes:

Type: 4-point, 6-point, e-commerce,
straight-line boxes
Robotic stacking: crashlock boxes
Minimum box width: 200mm
Maximum box width: 1200mm
Minimum box length: 140/200mm
Maximum box length: 800/1000/1200mm
Shingling overlap: Minimum 30mm

Robot bundle forming (crashlock):

Minimum box width: 200mm
Maximum box width: 1000mm
Minimum box length: 140mm
Maximum box length: 800mm

Bundle:

Minimum height before strapping: 50mm
Maximum height before strapping: 400mm (With a pre-press force of 5KG)
Maximum weight: 25kg

Speed:

Without robot bundle forming: Up to 1200 bundles/hour
With robot bundle forming: Up to 700 bundles/hour

Strapping machine:

Strapping Unit: Standard strapping machine
Strap width mm: 5-9-12-30(banding)
Quick exchange: Possible
Strap distance from bundle front end: Minimum 30mm
Strap distance from bundle rear end: Minimum 30mm

